

PE901

Power-over-Ethernet Injector



Description

The PE901 is a single port Mid-spans offer a compact and cost effective, fully IEEE 802.3af compliant solution for remote powering of wireless LAN (WAN) access points, IP Security cameras, VoIP telephone and other low port density installations. The PE901 PoE Mid-spans eliminate the need for external power supply and its associated AC/DC power cabling, providing a compact, affordable, safe and reliable power solution over existing Ethernet infrastructure.

Features

- Full IEEE 802.3af Compliant
- Up to 20W of Power on 2-pairs
- Auto-detect of POE IEEE 802.3af equipment
- Supports 10/100Base-T applications
- LED indicators power input indication
- Distance up to 100 meters
- Internal AC/DC converter – no need for external power brick
- Easy plug-and-play installation
- Surge protection
- EMI standards complies with FCC, CE class B

Specifications

Item	Description
No. of Ports	1
Pass Through Data Rates	10/100 Mbps
Power over Ethernet Output	Pin Assignment and Polarity: 3/6 (+), 1/2 (-) Output Power Voltage: 55Vdc User Port Power: 20W
Input Power Requirements	AC Input Voltage: 100 to 240 Vac AC Input Current: 0.2A 100-240 Vac AC Frequency: 50 to 60 Hz
Dimensions	150mmx65mmx38mm
Weight	
Indicators	System Indicator: AC Power User Indicator: Channel Power
Connectors	Shielded RJ-45, EIA 568A and 568B
Environmental Conditions	Operating Ambient Temperature: -10 to 45°C Operating Humidity: Maximum 90%, Non-condensing Storage Temperature: -20 to 70°C Storage Humidity: Maximum 95%, Non-condensing
Reliability	MTBF: 100,000 hrs. @25°C
Regulatory Compliance	IEEE 802.3af (PoE), RoHS Compliant, CE, FCC
Electromagnetic Emission & Immunity	FCC Part15, Class B EN 55022 Class B (Emissions) EN 55024 (Immunity), VCCI
Surge Protection	AC port: 6kV RJ45 port: 4kV
Safety Approvals	UL/cUL Per EN 6095-1 GS Mark Per EN 60950-1

Application

